


USB Schnell-Reiselader „Sama“ Fast Charger / Power Delivery-PPS



Input



Ultra Fast Charger



Total Power



Power Delivery
PPS

Produkt Info



Kompakter **Schnell-Reiselader** mit **USB Type-C™** Anschluss und **Power Delivery** und **PPS Schnellladetechnologie**. Die **intelligente Ladetechnologie** passt den Ladestrom an den Bedarf angeschlossener Geräte an, so dass die Optimale Versorgung zum schnellen Aufladen sicher gestellt ist. Der hochwertige Reiselader unterstützt alle Power Delivery kompatiblen Smartphones und lädt sie schnell und sicher auf. Nicht kompatible Geräte werden standardmäßig im 5V-Modus aufgeladen. Das Gerät bietet höchste **Sicherheit** gegen Überspannung-, Überlastung und Kurzschluss. Das Netzteil ist auch in weiß erhältlich.

Technische Daten:

- Modell: AC067PD
- Eingang: 100-240V AC
 - Ausgang Type-C:
 - PD: DC 5.0V 3.00A 15W oder 9.0V 2.77A 24.93W
 - PPS: DC 3.3-5.9V 3.00A 17.7W oder 3.3-11.0V 3.00A 25.0W
 - Gesamtleistung: 25.0 Watt
 - Durchschnittliche Effizienz im Betrieb: 81.4%
 - Effizienz bei geringer Last (10 %): 70.0%
 - Leistungsaufnahme bei Nulllast: 0.09 Watt
 - Abmessungen: 88.8 x 45.2 x 26.6 mm (inklusive AC-Stecker)

Black

Art.Nr: 260469

EAN: 4024559260469

White

Art.Nr: 260452

EAN: 4024559260452

Compact **fast travel charger** with **USB Type-C™** connection and **Power Delivery** and **PPS fast charging technology**. The **intelligent electronics** adapts the charging current to the demand of connected devices, so that the optimal supply for fast charging is ensured. The high-quality travel charger supports all Power Delivery compatible smartphones and charges them **quickly and safely**. Non-compatible devices are charged in 5V mode. The device offers **highest safety** against overvoltage, overload and short circuit. The charger is also available in white.

Technical data:

- Model: AC067PD
- Input: 100-240V AC
- Output Type-C:
 - PD: DC 5.0V 3.00A 15W or 9.0V 2.77A 24.93W
 - PPS: DC 3.3-5.9V 3.00A 17.7W or 3.3-11.0V 3.00A 25.0W
- Total Output: 25.0 Watts
- Average active efficiency: 81.4%
- Efficiency at low load (10%): 70.0%
- No-load power consumption: 0.09 Watts
- Dimensions: 88.8 x 45.2 x 26.6 mm (include AC pin)