

Reiseladegerät „Prim“ 5V-2.1A



Twin-USB-Reiselader zum Aufladen von Smartphones, Tablets und mobilen Telekommunikationsgeräten mit integriertem Akku mit bis zu 10,5 Watt Leistung. Eine LED informiert über den Betriebsstatus. Er ist zu allen Geräten kompatibel*, die über einen USB Anschluss geladen werden können und nicht mehr als 2.1 Ampere Strom ziehen. Der Adapter bietet höchste Sicherheit durch OVP, OCP und SCP.


Technische Daten:

- Modell: AC021 -52100
- Anschluss: USB-A Buchse
- Eingang : 100-240V AC
- Ausgang : 5V DC max. 2.1A
- Gesamter Ausgangsstrom für beide Ports: 2.1A;
Strom pro Ausgang: 2.1A max.
- Betriebs-LED: Orange
- Lager-/Betriebstemperatur: -20° bis +60° C
- Abmessungen: 81x55x29mm
- Gewicht: 60g

* Mit Apple Pin Konfiguration.

Art.Nr: LGUNTUSB2A

EAN: 4024559230035



Twin-USB-AC adapter to power smartphones, tablets and mobile telecommunication devices with integrated batteries with up to 10.5 Watts power. The LED informs about the operating status. It is compatible to all USB powered devices* drawing up to 2.1 Ampere. The adapter offers highest security by OVP, OCP and SCP.

Technical Specification :

- Model: AC021-52100
- Connection: USB-A Socket
- Input: 100-240V AC
- Output: 5V DC max. 2.1A
- Total output current for both ports: 2.1A;
Current per output: 2.1A max.
- Operation-LED: Orange
- Storage-/Operation temperature: -20° to +60° C
- Dimensions: 81x55x29mm
- Weight: 60g

*With Apple Pin Configuration

