


USB Ultra Schnell-Reiselader „GaNto30“ 30 Watt GaN Technologie – Fast Charge / PowerDelivery



Ultra Fast Charger



100-240V AC
Input



30 Watts
Total Power



USB-A
FC
Fast Charge



Type-C™
PD
Power Delivery



Safe & Protected

Produkt Info



Ultrakompakter, leistungsstarker Schnell-Reiselader mit USB-A und USB Type-C™ Anschluss zum schnellen Aufladen von allen Type-C und USB-A kompatiblen Geräten. Der USB-A Anschluss verfügt über Fast Charge Technologie und liefert 27 Watt Leistung. Der Type-C Anschluss ist mit Fast Charge und Power Delivery ausgestattet und liefert 30 Watt. Mit dem Reiselader GaNto können bis zu zwei Geräte gleichzeitig aufgeladen werden. Ihre Geräte werden nicht nur mit der maximalen Ladegeschwindigkeit aufgeladen, sie sind durch die Sicherheitsmechanismen des GaNto auch bestens geschützt. Die wichtigste Eigenschaft der verwendeten GaN Technologie, ist die sehr geringe Wärmeenergie. Dies ermöglicht eine sehr kompakte Bauweise mit einer hohen Leistungsdichte und Leistungskapazität entsprechend den Sicherheitsstandards.

Technische Daten:

- Eingangsspannung: 110-240V AC 50/60Hz 0.8A
- Ausgang USB-A (FC): DC 5.0V/3.0A/15.0W, 9.0V/3.0A/27.0W
12.0V/2.25A/27.0W
- Ausgang Type-C (PD): DC 5.0V/3.0A/15.0W, 9.0V/3.0A/27.0W,
12.0V/2.5A/30.0W, 15.0V/2.0A/30.0W,
20.0V/1.5A/30.0W, 3.3-16.0V (PPS)
- Gesamtleistung: 30.0 Watt
- Leistung bei gleichzeitiger Verwendung aller Anschlüsse: 30.0 Watt
- Kompatible Schnellladetechnologien: Quick Charge 3.0,
Power Delivery 3.0 (PPS), AFC, FCP, SCP
- Durchschnittliche Effizienz im Betrieb: 85,37%
- Effizienz bei geringer Last (10%): 79,67%
- Leistungsaufnahme bei Nulllast: 0.08W
- Abmessungen: 70.5 x 34 x 30mm (inklusive AC-Stecker)

Ultra-compact, powerful fast travel charger with USB-A and USB Type-C™ port for fast charging of all Type-C and USB-A compatible devices. The USB-A port features Fast Charge technology and delivers 27 watts of power. The Type-C port feature Fast Charge and Power Delivery and deliver up to 30 watts respectively. With the GaNto travel charger, up to two devices can be charged simultaneously with low heat and high efficiency. Your devices are not only charged at the maximum charging speed, they are also well protected by the safety mechanisms of the GaNto.

The most important feature of the GaN technology used, is the very low heat generation. This allows a very compact design with a high power density and power capacity according to safety standards.

Technical data:

- Input voltage: 110-240V AC 50/60Hz 0.8A
- Output USB-A (FC): DC 5.0V/3.0A/15.0W, 9.0V/3.0A/27.0W
2.0V/2.25A/27.0W
- Output Type-C (PD): DC 5.0V/3.0A/15.0W, 9.0V/3.0A/27.0W,
12.0V/2.5A/30.0W, 15.0V/2.0A/30.0W,
20.0V/1.5A/30.0W, 3.3-16.0V (PPS)
- Total power: 30.0 Watts
- Power when all ports are used simultaneously: 30.0 Watts
- Compatible fast charging technologies: Quick Charge 3.0,
Power Delivery 3.0 (PPS), AFC, FCP, SCP
- Average efficiency during operation: 85,37%
- Efficiency at low load (10%): 79,67%
- Power consumption at no load: 0.08W
- Dimensions: 70.5 x 34 x 30mm (include AC pin)

Art.Nr: 261367

EAN: 4024559261367

Art.Nr: 261350

EAN: 4024559261350

USB Type-C™ and USB-C™ are trademarks of USB Implementers Forum. Technische Änderungen vorbehalten / Improvement and changes of the technical specifications and other data's could be made without prior notice / Registered trademarks are the property of their respective owners.